


ERE10



PRO

EVERUN ERE10PRO

CRAWLER EXCAVATOR

EVERUN[®]
SINCE 2007

EVERUN[®]
SINCE 2007



EVERUN[®]
SINCE 2007

EVERUN[®]
SINCE 2007

Qingdao Everun Machinery Co.,Ltd

Address : Room 902, Yongxin International Finance Centre
No.6 Qinling Road, Qingdao, China

Tel : +86-532-80997859

Email : info@everun.cc

Fax : +86-532-80993178

Website : www.everun.com

Mobile: +86-18661725881

Youtube : [everunmachinery](https://www.youtube.com/everunmachinery)

Skype : [dylanchangcn](https://www.skype.com/dylanchangcn)



EVERUN ERE10PRO

CRAWLER EXCAVATOR

Standard Configuration

ERE10 Pro crawler excavator with 1000kg operating weight, 410mm bucket, canopy, changchai engine, Zaneda pump, Beifang valve, Hydro Man swing motor, head lights, Quick Hitch.

Technical Parameter

Operating Weight	1000kg	Chassis Width	870mm
Digging Bucket Capacity	0.023cbm/120kg	Track Width	180mm
Digging Bucket Width	410mm	Chassis Ground Clearance	94.5mm
Engine	CHANGCHAI-192FAM	Bucket Digging Force	9.7kn
Rated Power	7.5kw	Arm Digging Force	8.6kn
Displacement	6ml/r	Rubber Track Height	310mm
Bore Stroke	single cylinder, fan cool	Max. Digging Depth	1735mm
Main Pump	ZANEDA	Max. Vertical Digging Depth	1581mm
Pump Flow	18L/min	Max. Digging Height	3006mm
Valve	BEIFANG	Max. Dumping Height	2248mm
Swing Motor	Hydro Man(ZMP-1-200)	Max. Digging Radius on Ground	3224mm
Traveling Motor	EATON 612-4173-1	Min. Rotation Radius	1430mm
Overall Dimension(LxWxH)	3127x950x2195mm	Max. Upgrade Height of Bulldozer Blade	200mm
Wheelbase	920mm	Max. Digging Depth of Bulldozer Blade	200mm
Total Length of Track	1220mm	Boom Deflection Angle (Left)	30°
Platform Ground Clearance	380mm	Boom Deflection Angle (Right)	90°
Platform Back Turning Radius	810mm		